



Features

- **Triplex Multiplexing**
- Long period Time Lapse Recording
- **Remote Access**
Dialup, Local Area Network (LAN), Wide Area Network (WAN) Supports both Dynamic & Static IP
- High Resolution 640x480 Pixels
Recording / Viewing / Printing
- Event Trigger Recording
- **Intelligent Motion Detection**
- Alarm Turbo
- Instant Retrieval of Recordings
by "alarm event", "time index", "activity" or "on the fly" search
- Alarm History up to 10,000 records
- **Pan/Tilt/Zoom Control**
- Any Windows Compatible Printer
can be connected for image printing
- Watermark - Data encryption of recorded image prevents digital tampering.
- **Support both Dynamic & Static IP**

Advantages

- **All-in-One**
Slim combines video multiplexing, digital time-lapse recording, video motion detection, instant retrieval of image and remote video - all in one compact unit.
- **Easy to Operate**
Operated by Windows® Graphical User Interface and designed with state-of-art technology, Net168 is one user-friendly, stand-alone digital recorder.
- **Non-stop Recording**
Slim operates as a non-stop recorder even during playback, viewing or event searching.
- **Unattended Operation**
Slim allows unattended operation while recording and frees your staff to perform other security or managerial functions.

Specifications

MODEL	Net168 4CH	Net168 8CH
Camera Inputs	x 4	x 8
Video Output (Loop Through)	x 4	N/A
Alarm Input	x 4	x 8
Control Output	TTL x 4; NO/NC x 1	TTL x 8
Storage	80G, 120G, 160G	
AVI export media	CD RW, USB Device (Super Disk, Floppy)	
Resolution	640 x 480 pixels	
Recording Speed	Max. 30(NTSC)/25(PAL) frames/ second	
Display Speed	Max. 60 frames/ second	
Spot Mode		
Split Screen Mode	Max. 30(NTSC)/25(PAL) frames/ second	
Compression Ratio	600:1 (1.5K)	
Motion Detection	Full screen/camera, 4 sizable zone/camera	
Transmission Speed	2 - 4 Frames/Sec (PSTN) - Synchronized (LAN)	
Remote Access	PSTN, ISDN, TCP/IP, LAN, WAN, xDSL & etc....	
PTZ Control	PELCO, KALATEL, PANASONIC, KAMPRO	
Audio Recording (optional)	Stereo (L/R) x 1	
Dimension	335x435x45 (mm) , 13.18x17.13x1.77 (inch)	
Weight	N.W.:13.23LB(6kg), G.W.:17.64LB(8kg)	
Watch Dog	Hardware	
Watermark	Yes	
Operating Temperature	23°F to +113°F (-5°C to +45°C)	

Rear View



[<< BACK](#)

Telexper Incorporated

33235 Transit Avenue, Union City , CA 94587 USA

Phone:1-510-477-9150 Fax: 1-510-477-9644 E-mail: sales-us@telexper.com

Technical Support support-us@telexper.com

2003.03.04