



Transcorder



HotSwap



CDRW



System HDD



Features

- **Triplex Multiplexing**
Record, Playback and Archive simultaneously
- Long period Time Lapse Recording
- **Remote Access**
Dialup, Local Area Network (LAN), Wide Area Network (WAN) Supports both Dynamic & Static IP
- Dual Media Device
80, 120, 160, 200, 240, 280, 320, 360, 640 GB HDD
80 GB Hotswappable Backup HDD
- High Resolution 640x480 Pixels
Recording / Viewing / Printing
- Event Trigger Recording
- **Intelligent Motion Detection**
- Alarm Turbo
- **Smart Hotswappable Backup Management**
 - * Automatic Backup to Hotswappable Hard Drive
 - * Convenient Restoration Management
 - * Alarm Event Archiving
 - * Backup Hard Drive Change "buzzer" Reminder
 - * Backup Hard Drive Capacity "on-screen" indicator
- Instant Retrieval of Recordings
by "alarm event", "time index", "activity" or "on the fly" search
- Alarm History up to 10,000 records
- **Pan/Tilt/Zoom Control**
- Any Windows Compatible Printer

- can be connected for image printing
- Watermark - Data encryption of recorded image prevents digital tampering.
- High Speed recording - Up to 100 frames per second
- 4 sequential outputs

Advantages

- **All-in-One**
Tracker combines video multiplexing, digital time-lapse recording, video motion detection, instant retrieval of image and remote video - all in one compact unit.
- **Easy to Operate**
Operated by Windows® Graphical User Interface and designed with state-of-art technology, Thunder168 is one user-friendly, stand-alone digital recorder.
- **Non-stop Recording**
Tracker operates as a non-stop recorder even during playback, Backup Hard Drive change and viewing or event searching.
- **Unattended Operation**
Tracker allows unattended operation while recording and frees your staff to perform other security or managerial functions.
- **Super Integrated system**
Tracker provides 16 looping Camera inputs to connect to an additional viewing/ recording device.

Specifications

MODEL	Transcorder
Camera Inputs	8 or 16
Loop	8 or 16
Alarm Input	16
TTL Output	16
Resolution	640 x 480 pixels
Compression Ratio	600:1 (1.5K)
Storage	80G, 120G, 160G, 200G, 240G, 280G, 320G, 360G,640G
Backup Drive	80G, 120G, 160G
AVI export media	Floppy, Zip, USB CD R/W, USB Super Disk...
Operating Temperature	-5°C to +50°C, 23°F to +122°F
Remote Access	PSTN, ISDN, LAN, WAN, Mobile Phone
Transmission Speed	2 - 4 Frames/Sec (PSTN) - Synchronized (LAN)
Recording Speed	Max. 60(NTSC)/50(PAL) frames/ second
Display Speed Spot window Split Screen	60 Frame/sec Max. 60(NTSC)/50(PAL) frames/ second
Motion Detection	Full screen/camera, 4 sizable zone/camera
PTZ Control	PELCO, KALATEL, PANASONIC, KAMPRO
	Stereo (L/R) x 1

Audio Recording (optional)	
Watch Dog Timer	Hardware
Dimension	453x430x111 (mm) , 17.83x16.93x4.37 (inch)
Weight	N.W.:33.07LB(15kg), G.W.:41.89LB(19kg)
Sequencer	4 Outputs
Watermark	Yes

 **Rear View**



[<< BACK](#)

Telexper Incorporated

33235 Transit Avenue, Union City , CA 94587 USA

Phone:1-510-477-9150 Fax: 1-510-477-9644 E-mail: sales-us@telexper.com

Technical Support support-us@telexper.com

2003.03.04